Material Safety Data Sheet				
SPAGUARD® OXIDIZ	ER ENHANCED SHOCK			
Version: 1.1	Revision Date: 12/27/2010	Print Date: 05/31/2012		
SECTION 1. PRODUCT AND CO	MPANY IDENTIFICATION			
Product name:	SPAGUARD® OXIDIZER ENHANCE	D SHOCK		
Product Use Description:	Recreational Water Product			
Chemical nature:	Chlorinated Isocyanurates			
Registration number:	5185-475			
Company:	Bio-Lab, Inc. BioGuard P.O. Box 300002 Lawrenceville, GA 30049-1002			
	Telephone: (800) 859-7946			
Emergency telephone number:	CHEMTREC: (24 hours) 800-424-9300, 703- Poison Control Center (Medical) :: (877) 800- Chemtura Corporation Emergency Response:	5553		
	For additional emergency telephone numbers	see section 16 of the Safety Data Sheet.		
Prepared by:	Product Safety Department (US) +1 866-430-2775			
	+011-886-2-2712-5668 MSDSRequest@c	hemtura.com		

## **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Г

Form: granules	Colour: white	Odour: Chlorine		
	:			
Hazard Summary	Corrosive			
	Oxidizer Causes serious eye damage. Harmful if swallowed.			
	Harmful if absorbed through skin.			
	Avoid breathing dust or vapor.			
	Irritating to skin. May be harmful if inhaled.			
	•	ensitization by skin c	ontact.	
5.0	1/1	-	SDS Number: 00000004806	

SPAGUARD® OXIDIZ		Material Safety Dat HANCED SHOCK	a Sheet	
/ersion: 1.1		Revision Date: 12/27/	/2010	Print Date: 05/31/2012
	Do	not get in eyes, on skin, o	or on clothing.	
OSHA Hazards	FEI	IS MATERIAL IS HAZA DERAL OSHA HAZARI 0.1200.		
Potential Health Effects				
Primary Routes of Entry	Eye Inha	n contact contact alation estion		
Aggravated Medical Condition		piratory disorders disorders		
Inhalation	: Cau	ses respiratory tract irritatio	n.	
Skin	May On o	ises skin irritation. v cause allergic skin reaction contact with moisture, this n urns if not promptly remove	naterial readily hydrolyz	zes to acid which may result
Eyes	: Cau	ses serious eye damage.		
Ingestion	: Harı	mful if swallowed.		
Chronic Exposure	anin Whe	product contains a boron on nals at very high doses, has en this product is used acco product does not represent	s shown reproductive an ording to label directions	s, the boron compound in
ECTION 3. COMPOSITION/INI Hazardous components	ORMATIC	ON ON INGREDIENTS		
Component			CAS-No.	Weight percent
Sodium Dichloro-S-Triaz	inetrione		2893-78-9	58.2 %
sodium persulfate			7775-27-1	15 - 25 %
aluminium sulfate			10043-01-3	5 - 15 %
Boron salt	Boron salt			5 - 15 %

SAP 6.0

rsion: 1.1	Revision Date: 12/27/2010 Print Date: 05/31/2012			
CTION 4. FIRST AID MEASUR	ES			
First aid procedures				
Inhalation	:	: Remove to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a POISON CENTER or doctor/ physician.		
Skin contact	:	Remove contaminated clothing and shoes. Rinse immediately with plenty of water for at least 3 Call a POISON CENTER or doctor/ physician.	30 minutes.	
Eye contact	:	Rinse immediately with plenty of water, also under minutes. Remove contact lenses, if present, after 5 minutes, Call a POISON CENTER or doctor/ physician.	-	
Ingestion	:	Call a physician or poison control centre immediate Have person sip a glass of water if able to swallow. DO NOT induce vomiting unless directed to do so b control center. Do not give anything by mouth to a convulsing or un	by a physician or poison	
Notes to physician				
Treatment	:	Probable mucosal damage may contraindicate the	use of gastric lavage.	
CTION 5. FIRE-FIGHTING ME	ASL	IRES		
Flammable properties				
Flash point	:	Remarks: not applicable		
Fire fighting				
Suitable extinguishing media	:	Flood with large volumes of water.		
Unsuitable extinguishing media	:	: ABC powder Dry powder Risk of violent reaction.		
Further information	<ul> <li>When ignited, will burn with the evolution of noxious chlorine containing gases. Do not let fire burn.</li> <li>Oxidizer Test Results: This product was not classified as an oxidizer when tested by the UN Oxidizer Test.</li> <li>Nitrogen trichloride can be generated slowly by the reaction of small quantities of water with a high concentration of this product. Nitrogen trichloride can present an explosion hazard. Immediately after a fire has been extinguished, check for wet or damp material. Any spilled material from burned or broken containers should be assumed contaminated. Neutralize to a non-oxidizing material for safe</li> </ul>			
6.0		- / / /	r: 000000004806	

sion: 1.1		Revision Date: 12/27/2010	Print Date: 05/31/2
disposal. Do not attempt to re-close broken containers, even for movement to the disposal area. They should be left open to disperse any nitrogen trichloride that may form. Material which appears undamaged except for being damp on the outside, should be opened and inspected immediately. If the plastic liner (where applicable) of the container is damaged or the material is damp, the material should be chemically treated if allowable, to a non-oxidizing material for safe disposal. Bulging containers require extreme care. Contact the fire department.			
Protective equipment and pr	rec	autions for firefighters	
Specific hazards during fire fighting	:	Under extreme heat (greater than 400F), this pr containing gases.	oduct will evolve noxious chlorine
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathin Thoroughly decontaminate fire fighting equipme wearing apparel after the incident.	
TION 6. ACCIDENTAL RELE	AS	EMEASURES	
Environmental precautions	:	Do not flush into surface water or sanitary sewe	r system.
Methods for containment / Methods for cleaning up	:	Clean-up methods - large spillage Using appropriate protective clothing and safety material. Do not add water to spilled material. Using clean dedicated equipment, sweep and s contaminated soil, and other contaminated mate containers for disposal. Do not close containers containing wet or damp open to disperse any hazardous gases that may Clean-up methods - small spillage In case of spills, scoop up and place product in spilled area with large volumes of water.	coop all spilled material, erial and place into clean dry material. They should be left / form.
Additional advice	:	Do not use floor sweeping compounds to clean Do not transport wet or damp material. Treat recovered material as described in the set Do not contaminate water, food or feed by stora equipment.	ction "Disposal considerations".
TION 7. HANDLING AND STO	DR/	AGE	
Handling			
Handling procedures	:	Avoid contact with skin, eyes and clothing. Avoid breathing dust. Avoid breathing vapors. Contains a strong oxidizing agent.	
		Do not mix with other chemicals. Mix only with water.	

ersion: 1.1	Revision Date: 12/27/2010	Print Date: 05/31/20
	<ul> <li>Never add water to this product.</li> <li>Always add product to large quantities of water.</li> <li>Use only clean and dry utensils.</li> <li>Do not add this product to any dispensing devices containing remnants of a other product. Such use may cause a violent reaction leading to fire or explosion.</li> <li>Contamination with moisture, organic matter or other chemicals may start a chemical reaction and generate heat, hazardous gas, possible fire and explosion.</li> <li>In case of contamination or decomposition, do not reseal container.</li> <li>Flood with large volumes of water.</li> <li>Wash hands thoroughly with soap and water after handling and before eatidrinking or using tobacco.</li> <li>Do not handle until all safety precautions have been read and understood.</li> </ul>	
Storage		
Requirements for storage areas and containers	<ul> <li>Keep containers tightly closed in a dry, cool and well-v For bags: Store dry product in its original unopened ba used bags, fold over top of bag and secure with adhes For bottles: Store dry product in orginal tightly closed Keep out of reach of children. Keep away from animals.</li> </ul>	ag until use. For partially vive tape.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Guidelines**

## Components with workplace control parameters

Components / CAS-No.	Value / Basis / Update	Control parameters	Further information
Boron salt	TWA	10 mg/m3	
	OSHA P0		
	1989-01-19		
	TWA	2 mg/m3	
	ACGIH		
	2007-01-01		
	STEL	6 mg/m3	
	ACGIH		
	2007-01-01		

Engineering measures			
Engineering measures	: Use with adequate ventila Ensure that eyewash station location.	tion. ons and safety showers are close to the workstation	
SAP 6.0	5 / 11	SDS Number: 00000004806	l

Version: 1.1	Revision Date: 12/27/2010	Print Date: 05/31/2012

## Personal protective equipment

Eye protection	: Safety glasses with side-shields
Hand protection	: For prolonged or repeated contact use protective gloves. Wear rubber gloves. not required under normal use
Respiratory protection	: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
Hygiene measures	: Wash contaminated clothing before reuse.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

## Appearance

Form Colour	: granules : white
Odour	: Chlorine
Safety data	
Flash point	: Note: not applicable
рН	: 5 - 5.5 Note: 1% Solution
Melting point/range	: 522 °F (272 °C)
Boiling point/boiling range	: Note: not applicable
Vapour pressure	: Note: no data available
Density	: 1.0 g/cm3
Water solubility	: 250 g/l
Relative vapour density	: Note: Not Available
SECTION 10. STABILITY AND	REACTIVITY

Conditions to avoid	: Remarks: High temperatures. Poor ventilation.	
SAP 6.0	6 / 11	SDS Number: 00000004806

# Material Safety Data Sheet

	ER ENHANCED SHOCK	
ersion: 1.1	Revision Date: 12/27/2010	Print Date: 05/31/20
	Contamination Moisture/high humidity.	
Materials to avoid	: Remarks: Avoid contact with water on concentrate container. Avoid contact with easily oxidizable mat similar nitrogen containing compounds; inorganic of floor sweeping compounds; calcium hypochlorite; chemicals in their concentrated form; alkalis. Avoid chemicals.	terial; ammonia, urea, or reducing compounds; other swimming pool/spa
Hazardous decomposition products	: Note: Chlorine containing gases can be produced.	
Hazardous reactions	: Hazardous polymerisation does not occur.	
CTION 11. TOXICOLOGICAL	INFORMATION	
Acute oral toxicity	: LD50: 599 mg/kg Species: rat	
	: LD50: 862 mg/kg Species: rat	
Acute inhalation toxicity Sodium Dichloro-S- Triazinetrione	: LC50: 0.27 - 1.17 mg/l Exposure time: 4 h Species: rat	
Boron salt	: LC50: 0.27 - 1.17 mg/l	
Acute dermal toxicity	: LD50: ca. 5,000 mg/kg Species: rat	
Skin irritation	: Remarks: Irritating to skin.	
Eye irritation	: Remarks: Corrosive - causes irreversible eye dam	nage.
Sensitisation	: Remarks: Repeated or prolonged skin contact may reactions with susceptible persons.	y cause allergic
Toxicology Assessment		
CMR effects	: Mutagenicity:	

P 6.0	7 / 11	SDS Number: 00000004806
CMR effects	sulfate, a component of this	lable for the product, although aluminum product, has been shown to cause mmalian chromosomal aberration test in

SAP 6.0

Material Safety Data Sheet PAGUARD® OXIDIZER ENHANCED SHOCK		
sion: 1.1	Revision Date: 12/27/2010	Print Date: 05/31/2
	human lymphocytes, but is not mutagenic in other in vitro tests. There is no indication that aluminum sulfate is carcinogenic or affects fertility. When this product is used according to label directions, the aluminum sulfate in this product does not present a practical health risk. (EN)	
ECOLOGICAL INFORMAT	ION	
Tovicity to fich		
Toxicity to fish sodium persulfate	: LC50: 771 mg/l Exposure time: 96 h	
	Species: Lepomis machrochirus (Bluegill)	
	static test	
aluminium sulfate	: LC50: 37 mg/l Exposure time: 96 h	
	Species: Gambusia affinis (Mosquito fish) static test	
	LC50: 33.9 mg/l	
	Exposure time: 96 h	
	Species: Pimephales promelas (fathead minnov flow-through test	N)
Toxicity to daphnia and ot	ner aquatic invertebrates.	
sodium persulfate	: EC50: 133 mg/l	
	Exposure time: 48 h Species: Daphnia magna (Water flea)	
	Species. Daprilla magila (Water liea)	
aluminium sulfate	: LC50: ca. 6.57 mg/l	
	Exposure time: 48 h	
Boron salt	: > 100 mg/l	
	Exposure time: 48 h	
	Species: Daphnia magna (Water flea)	
Toxicity to algae		
Toxicity to algae Boron salt	: > 100 mg/l	
	Exposure time: 72 h	
	Exposure time: 72 h	
Boron salt	Exposure time: 72 h Species: Algae : Remarks:	
Boron salt Bioaccumulation	Exposure time: 72 h Species: Algae	
Boron salt Bioaccumulation aluminium sulfate Further information on e	Exposure time: 72 h Species: Algae : Remarks: Bioaccumulation is unlikely.	
Boron salt Bioaccumulation aluminium sulfate	Exposure time: 72 h Species: Algae : Remarks: Bioaccumulation is unlikely.	

	Revision Date: 12/27/2010	Print Date: 05/31/20
	Do not discharge effluent containing this product into streams, ponds or estuaries, oceans, or other waters accordance with the requirements of a National Pollu Discharge Elimination System (NPDES) permit and the authority has been notified in writing prior to discharge discharge effluent containing this product to sewer sy without previously notifying the local sewage treatme authority. For guidance contact your State Water Bo Regional Office of the EPA. Do not use treated pool water on plants or lawns as the and other pool chemicals could cause damage. (EN)	s unless in utant he permitting ge. Do not ystems ent plant aard or this product
CTION 13. DISPOSAL CONSI	DERATIONS	
Further information	<ul> <li>Improper disposal of excess product, spray mixture or violation of Federal Law.</li> <li>If these wastes cannot be disposed of by use according instructions, contact your Environmental Control Age Hazardous Waste Representative at the nearest EPA Office for guidance. For registered pesticides, contact Pesticide Agency.</li> <li>Do not put product, spilled product, or filled or partiall containers into the trash or waste compactor.</li> <li>Contact with incompatible materials could cause a registered pesticide cause a registered pesticide cause a registered pesticide cause a registered with incompatible materials could cause a registered cause a registered with incompatible materials could cause a registered with incompatible materials could cause a registered cause a registered with incompatible materials could cause a registered cause a registered with incompatible materials could cause a registered with incompatible materials could cause a registered with incompatible materials could cause a registered with incompatible materials cause a</li></ul>	ing to label ency or the A Regional ct your State ly filled
Contaminated packaging	<ul> <li>Do not re-use empty containers.</li> <li>Rinse thoroughly before discarding in trash.</li> <li>Offer rinsed packaging material to local recycling facility</li> </ul>	ilities.
CTION 14. TRANSPORT INFO	DRMATION	
<b>DOT</b> Not dangerous goods		
Not dangerous goods	: 1759	
Not dangerous goods <u>IATA</u> UN number Description of the goods	<ul> <li>Corrosive solid, n.o.s.</li> <li>(SODIUM DICHLORO-S-TRIAZINETRIONE)</li> </ul>	)
Not dangerous goods <u>IATA</u> UN number	Corrosive solid, n.o.s.	)
Not dangerous goods           IATA           UN number           Description of the goods           Class           Packing group           IMDG	<ul> <li>Corrosive solid, n.o.s. (SODIUM DICHLORO-S-TRIAZINETRIONE)</li> <li>8</li> <li>II</li> </ul>	)
Not dangerous goods <u><b>IATA</b></u> UN number Description of the goods Class Packing group	<ul> <li>Corrosive solid, n.o.s.</li> <li>(SODIUM DICHLORO-S-TRIAZINETRIONE)</li> <li>8</li> </ul>	

PAGUARD® OXIDIZ	Material Safety Data Sheet ZER ENHANCED SHOCK	
rsion: 1.1	Revision Date: 12/27/2010	Print Date: 05/31/2
Class Packing group EmS Letter 1 EmS Letter 2 Marine pollutant	<ul> <li>8</li> <li>II</li> <li>F-A</li> <li>S-B</li> <li>yes SODIUM DICHLORO-S-TRIAZINETRIONE</li> </ul>	
Not recommended for shi Not regulated by DOT and by road and/or rail.		
CTION 15. REGULATORY IN		
OSHA Hazards	: This material is hazardous under the criteria of the Fe Communication Standard 29CFR 1910.1200.	ederal OSHA Hazard
CERCLA Reportable	: 5000 lbs	
Quantity SARA 311/312 Hazards	: Acute Health Hazard Fire Hazard Reactivity Hazard	
The components of this p	oduct are reported in the following inventories:	
EINECS	On the inventory, or in compliance with the inventory	
TSCA	On TSCA Inventory	
AICS	Not in compliance with the inventory	
DSL	All components of this product are on the Canadian DSL list.	
PICCS	On the inventory, or in compliance with the inventory	
IECSC	On the inventory, or in compliance with the inventory	
6.0	10 / 11 SDS Number	: 00000004806
0.0		: 00000004606

	Material Safety Data Sheet	
SPAGUARD® OXIDIZER ENHANCED SHOCK		
Version: 1.1	Revision Date: 12/27/2010	Print Date: 05/31/2012
SECTION 16. OTHER INFORM	ΙΑΤΙΟΝ	
Further information		
HMIS Classification	<ul> <li>Health hazard: 3 Flammability: 0 Physical hazards: 1 PPI:Ask supervisor or safety specialist for handling</li> </ul>	instructions
NFPA Classification	: Health hazard: 3 Fire Hazard: 0 Reactivity Hazard: 1 Specific hazards: OX Class 1 Oxidizer.	

#### **Other Emergency Phone Number**

Latin America:	Brazil	+52 113 711 91 44
	All other countries	+44 (0)208 762 8322
Mexico:		+52 555 004 87 63

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.